



TECHNICAL DATA

Dehumidifier model

DC-031B

DC-031C-16A


|                              |                       |                       |
|------------------------------|-----------------------|-----------------------|
| Nominal capacity *           | 1.4 kg/h              | 2.1 kg/               |
| Dry air flow**               | 300 m <sup>3</sup> /h | 490 m <sup>3</sup> /h |
| Wet air flow **              | 120 m <sup>3</sup> /h | 120 m <sup>3</sup> /h |
| Heater current***            | 8 A                   | 13 A                  |
| Maximum electric consumption | 2.1 kW                | 3 kW                  |
| Supply fuse 230V / 50Hz      | 10 A                  | 16 A                  |
| Weight                       | 30 kg                 | 32 kg                 |

\* Valid for inlet conditions 20°C/60%RH. For other inlet conditions, the capacity can be calculated by using the correction factor from the diagram shown below.

\*\* Volume flow for density 1.20 kg/m<sup>3</sup>. Free blowing

\*\*\* Thanks to the thermistor heater, the power can be steplessly varied by controlling the wet air flow.

CORRECTION DIAGRAM




The temperature of the dry air at nominal air flows is calculated by:

$$t_{out} = t_{in} + ((K \times 9) + 5)$$

The dehumidifying capacity is estimated as the nominal capacity from above, multiplied by factor (K) from the correction diagram.

DIMENSIONS



Subject to change without notice.

Seibu Giken DST AB

Avestag, 33, S-163 53 Spånga,  
Sweden www.dst-sg.com  
E-mail: info@dst-sg.com  
tel: +46-8 4457720; fax: +46-8 4457739

Representative: